

## Dimensions of the print data

Please create the printing file according to your format selection on the product page. The shown size in this guideline is just an example.



## Summary



File format incl. 0.12" bleed Example: 16.24" x 23.24"

Visible final format Example: 16" x 23"

#### Our recommendation

We recommend a safety distance of at least 0.12" for fonts, logos or others important elements, because we cannot provide a 100% guarantee for the accuracy for the cut.

#### Important

Please create the data *without* trim and crop marks. Further information can be found on *page 2*.

# ARTWORK Guideline Posterprint



## **File settings**

Format: Resolution:	final format or ratio 1:1 ratio 1:2 ratio 1:10	r scaled (e.g. 1:2) 96-150 dpi 192-300 dpi 960-1500 dpi
Bleed:	0.12"	
Crop marks: Overprint: Fonts:	no deactivated embedded or converted to paths	
Do not use:	clipping paths, alpha channels, masks in TIFF / JPG	



## File formats

#### Please use:

- From PDF X-3\*

#### \*important notice

Printing files can be created in a variety of different programs with different attributes. This way, numerous errors may occur: for instance missing or incorrect fonts, color anomalies, missing images etc. To avoid this **please create your data as a print-ready PDF / X-3:2002.** 





## Colors

## Color mode: Color profile:

U.S. Web Coated (SWOP) V2, ISO Coated v2, Coated Fogra 27/39

#### Do not use:

RGB and spot colors such as Pantone, HKS and RAL as they will be converted to CMYK. We cannot guarantee color accuracy for converted colors.

## File upload



#### Upload to our server

www.werbecenter-onlineshop.de Please sign up for an online account and upload the files for the ordered product to your latest order.

### Notes

- $\cdot\,$  Print and production tolerance will be 0,25%
- $\cdot\,$  We can't guarantee measurements exact to 0.-inch

CMYK

 Depending on color profile, print material and the use of different file formats for similar motifs, colors may vary